MDE/PARTICLE BOARD

DIVISION 6: WOOD & PLASTICS

and the test	Environmental Certificates Recycled Content Pollutants													
					Environmental Certificates				Recycled Cont	ent		Pollutants		
Material		Manufacturer's Product Line	FSC	SFI		SCS Recycled Certification		CARB ATCM	Cumulative RC	Post- consumer	Post- industrial	No Formaldehyde	Warranty	Notes
			Yes, No, N/A,	Yes, No, N/A, Optional	Yes, No	Yes, No	Score	Yes, No	%	%	%			
MDF	West Fraser	WestPine & Ranger Board	Y	Y	Y	Y	-	Y	43-45%	0%	86-90%	х	N	
MDF	Roseburg (prev. Sierra Pine)	Arreis, PermaCore, Medex & Medile II	0	N	N	Y	-	Y	46%	0%	92%	х	90 days	
PB	Tafisa Canada Inc.	TAFIPAN & TAFIPAN+ EVOLO™	Y	N	N	Y	-	Y	50%	0%	100%	х	N	
PB	Plummer Forest Products	EnStron Industrial	Y	N	N	N		Y	50%	0%	100%	х	N	
MDF	<u>UniBoar</u> d	NU Green 2 MDF	Y	N	N	N		Y	50%	0%	100%	х	N	
РВ	Roseburg	UltraBlend Particleboard	Y	N	N	Y	-	Y	50%	0%	100%	х		Meets CARB ATCM 93120 Phase 2 emission limits
PB	Arauco	Duraflake VESTA ULEF	Y	N	N	N	-	Y	50%	0%	100%	х	N	

OSB/PL	YWOOD												
					Environmental Certificates			Recycled Cont	ent		Pollutants		
Material	Manufacturer	Manufacturer's Product Line	FSC	SFI	CSA	SCS Recycled Certification	CARB ATCM	Cumulative RC	Post- consumer	Post- industrial		Warranty	Notes
			Yes, No, N/A,	Yes, No, N/A, Optional	Yes, No	Yes, No	Yes, No	%	%	%			
OSB	Georgia Pacific	Blue Ribbon OSB Sheathing & Flooring	Y	Y	N	N	N	0%	0%	0%	х	Lifetime Limited	
OSB	Huber	Huber Blue Flooring and Sheathing	Y	N	N	N	N	0%	0%	0%	x	25 year limited	
PLY	Roseburg	Super Ply	Y	N	N	N	N	0%	0%	0%	х	N/A	
PLY	Georgia Pacific	Plytanium	Ŷ	Y	N	N	Exempt*	0%	0%	0%	X	Limited	*Interior grade products contain no added urea formaldeh yde.
PLY	Potatch.	Precision Core Plywood	Y	N	N	N	N	0%	0%	0%	x	25 year limited	
PLY	Columbia Forest Products	PureBond	Y	N	N	N	Y	0%	0%	0%	х	N/A	

Wood Plastic/Plastic											
					Environmental	Certificates			Recycled Content		
Material	Manufacturer	Manufacturer's Product Line	FSC	SFI	CSA			Combined		Post-industrial (median)	Warranty
			Yes, No, N/A	Yes, No, N/A or	Yes, No	Yes, No	Yes, No	%	%	%	Years
High Density Polyethylene	PlasTEAK	PlasTEAK	N/A	N/A	N/A	N/A	N	91%	91%	0%	20
High Density Polyethylene	Resco Plastics	HDPE Decking	N/A	N/A	N/A	N/A	N	83%	65%	35%	50
Wood Plastic	Fiberon	Horizon Decking	N	N	N	N	N	78%	74%	8%	25
Wood Plastic	Trex	Trex Transcend	N	N	N	N	N	75%	55%	40%	25
High Density Polyethylene	EPS Plastic Lumber	Bear Board	N/A	N/A	N/A	N/A	N	51%	51%	0%	50

Tropical or Domestic Hard	wood				
Materia I	Material	Manufacturer	FSC	WARRANTY	EXTERIOR LIFE EXPECTANCY
Domestic, North Eastern US	Black Locust Decking		Y		Determined by the USDA Forest Service to have Exceptionally High Decay Resistance (beyond Cedar & Oak)
Domestic, North Eastern US	White Cedar decking		Y		15 years, USDA Forest Service Decay Resistant
Domestic, North Eastern US	White Oak		Ŷ		10 - 15 years, USDA Forest Service Decay Resistant
Domestic, South Eastern US	Thermally Modified Pine	EcoVantage: Eco D eck		30 Year Limted Mateiral Warranty against Decay	
Tropical, South America	lpe, Cumaru, Garapa Decking		Y		Many distributors of Ipe & similar tropical hardwoods will guarantee their lumber products for at least 20 $-$ 25 years

General Constru	ction										
							Environmental Certificates	Pollutants			
Manufacturer	Material	Manufacturer's Product Line	Material Applications (ex: wood to wood, wood to metal, vinyl, frp, wallpaper, laminate, etc.)	Installation Method	Construction Application	Material Base (ex: water or solvent)	Greenguard	No-VOC	Low-VOC	Warranty	Notes
Lochie	Acrylic	Power Grab	Bonds a variety of construction materials	Gun	Interior (exterior formulation available)	**Water Based	YES		48.13 g/L		
Tilebond	Polymer Blend	Green Choice Heavy Duty Construction Adhesive	Bonds a variety of construction materials including: paneling, plywood, lumber, foamboard, plastics, etc.	Gun	Interior/ Exterior Construction	Solvent Free			38.85 glL		Part of Titebond's GreenChoice Adhesive product line.
Loctile	Synthetic Rubber & Resin (unknown)	Loctite® PL® 375 Heavy Duty Construction Adhesive	Bonds a variety of materials (not recommended for use with polystyrene or abs panels and foams)	Gun	Interior/ Exterior Construction	**Water Based	NO		49 g/L		
Liquid Nails	Latex	Drywall Adhesive DWP-24	For interior drywall construction	Gun	Interior Construction	(Water Clean Up)	YES		32 g/L	(Manufacturer warrants satisfaction of product)	
Liquid Nails	Latex	Interior Projects Adhesive Low- VOC (LN-704 / LNP-704)	Bonds a variety of construction materials	Gun	Interior Construction	(Water Clean Up)	YES		35 g/L	(Manufacturer warrants satisfaction of product)	
Titebond	Polyurethane	Titebond Fast Set Polyuerethan Construction Adhesive	Bonds a variety of construction materials including: plastics, foam, lumber and non- porous materials.	Gun	Interior/ Exterior Construction	Solvent	NO		20 g/L		Part of Titebond's GreenChoice Adhesive product line.
Locille	Polyurethane	Loctite® PL® Premium Polyurethane Construction Adhesive	Bonds a variety of construction materials including: hardwood flooring, stone, concrete, masonry, carpet, etc. (not recommended for polystyrene, polyethytene or polypropytene.)	Gun	Interior/ Exterior Construction	Solvent	NO		45 glL		

Joint Sealants (Ad	crylic & Silicone)										
							Environmental Certificates	Pollutants			
Manufacturer	Material	Manufacturer's Product Line	Material Applications (ex: wood to wood, wood to metal, vinyl, frp, wallpaper, laminate, etc.)	Installation Method	Construction Application	Material Base (ex: water or solvent)	Greenguard	No-VOC	Low-VOC	Warranty	Notes
Eco-Bond Adhesives	Silicone	Multi Purpose Adhesive/Sealant(previous product	effective bond on most materials	Gun	Interior/ Exterior Construction	Silicone	NO	VOC Free			
<u>3M</u> .	Acrylic	Weatherban Acrylic Sealant 606 - NF	variety of materials	Gun	Interior/ Exterior Construction	Water Based	NO		**17 g/L		
DAP	Acrylic Latex with Silicone	**Alex Plus Clear	wood, brick, glass, metal, plaster, drywall, painted surfaces	Gun	Interior/ Exterior Construction	(water clean up)	NO		38 g/L		
GE Silicones	Silicone		variety of materials including: glass, ceramic, steel, granite, aluminum, plastics	Gun	Interior/ Exterior Construction	Silicone	NO		23 g/L		
Dow Corning	Silicone	795 Silicone Building Sealant	effective bond on most materials	Gun	Interior/ Exterior Construction	Silicone	NO		28 g/L		
Sherwin Williams	Polyurethane	Loxon S1 One Component Smooth Polyurethane Sealant	for use on a variety of materials	Gun	Interior / Exterior Construction	Solvent	YES		68 g/L	If used within one year of purchase, SW will warrant the products performance	

Flooring / Tile Adl	hesives : Carpet										
							Environmental Certificates	Pollutants			
Manufacturer	Material	Manufacturer's Product Line	Material Applications (ex: wood to wood, wood to metal, vinyl, frp, wallpaper, laminate, etc.)	Installation Method		Material Base (ex: water or solvent)	Greenguard	No-VOC	Low-VOC	Warranty	Notes
WF Taylor	Latex	2056 Super Premium Commercial Carpet Adhesive	can be used to adhere a variety of carpet backing types.	Trowel	Interior	Latex	YES		Low VOC		
WF Taylor	Latex	2090 Meta-Tec Vinyl Back Floor Covering Adhesive	developed for vinyl back flooring and carpet	Trowel	Interior	Acrylic	YES		Low VOC		
Mapei	Synthetic Polymer	Ultrabond ECO 185	can be used to adhere a variety of carpet backing types.	Trowel	Interior	Water Based	NO		"Low VOC (14 g/L)	1 year performance warranty	
			*Carpet Manufacturers, Manning	ton, Lees, Milliken and Tandus	distribute their own brand of adh	esive with carpet orders.	Data and MSDS sheets are available				


Flooring / Tile Ad	dhesives : Tile/Wood											
								Environmental Certificates	Pe	llutants		
lanufacturer	Material	Manufacturer's Product Line	Material Applications (ex: wood to wood, wood to metal, vinyl, frp, wallpaper, laminate, etc.)	Installation Method	Construction Application	Material Base (ex: water or solvent)	Greenguard	Other Environmental Certificates	No-VOC	Low-VOC	Warranty	Notes
ostik	Urethane	Wood-Grip ™ Advanced ™	general purpose wood flooring adhesive	Trowel	Interior	Solvent Free	NO		VOC Free			
ona	Silane	Bona R851 Wood Flooring Adhesive	general purpose wood flooring adhesive	Trowel	Interior	Silane Based	YES	California Proposition 65 Compliant	VOC Free			
apei	Urethane	Ultrabond ECO/8 980	engineered, solid wood, acrylic impregnated wood/laminated plank, concrete (except below-/on- grade concrete without functional vapor barrier	Trowel	Interior	Solvent Free	NO			37 g/L	Lifetime bond performance warranty	
orbo	Acrylic	T 940	Marmoleum tile (will bond to concrete, wood and resilient underlayment)	Trowel	Interior	Water Based	NO	FloorScore	VOC Free			
I.W. Henry	Acr ylic	582 LinoLock)	linoleum sheet flooring (will bond to concrete, wood metal, ceramic underlayment and will bond to existing resilient flooring)		Interior	Solvent Free	ND			5 g/L	10 year warranty covering material / bond performance.	
<u>ost</u> ik	Urethane	Bostik's Best Wood Flooring Urethane Adhesive	engineered, solid, finished, unfinished wood flooring (concrete and all wood based underlayment)	Trowel	Interior	Solvent	NO			20 g/L	Limited Warranty	mold / mildew resistar
<u>ost</u> ik	Acrylic Co-polymer Latex	D-2001® Ultra-Premium	ceramic, natural stone tile (except moistuire sensitive marble)	Trowel	Interior	water clean up (if cured), mineral spirits clean up (if uncured)	ND			<30 g/L		
I.W. Henry		Henry 314 ReadySet Premixed Mastic Adhesive	ceramic, natural stone tile	Trowel	Interior	Water Based	NO			60 g/L	10 year warranty covering material / bond performance.	
tesilient / Rubbe	er Flooring Adhesives	(Urethane)										
							Environmental Certificates		Po	llutants		
lanufacturer	Material	Manufacturer's Product Line	Material Applications (ex: wood to wood, wood to metal, vinyl, frp, wallpaper, laminate, etc.)	Installation Method	Construction Application	Material Base (ex: water or solvent)	Greenguard	CRI Green Label	No-VOC	Low-VOC	Warranty	Notes
<u>st</u> ik	Urethane	GreenFusion Rubber Flooring Adhesive	rubber flooring: will bond to concrete, asphalt, plywood and terrazzo	Trowel	Interior	Solvent Free	NO		VOC Free		Limited Warranty (free from defects & meets	
apei	Urethane	Ultrabond P990 1K	cork (bonds to concrete and all wood based underlayment)	Trowel	Interior	Solvent Free	NO	NO		**18 gL	Limited matching lifetime floor warranty	
<u>ost</u> ik	Urethane	BST™	Cork, solid hardwood, engineered hardwood, bamboo, parquet, plywood, ceramic tile, marble and stone in lavs	Trowel	Interior	Solvent	NO	ND		22 g/L	Limited Warranty	mold / mildew resistar

Blanket															
				Environme	ntal Certificates			Recycled Content			Polit	utants			
Material	Manufacturer	Manufacturer's Product Line	Pharos	SCS Indoor Advantage Gold	SCS Recycled Content	Greenguard	Total	Post- consumer (median)	Post- industrial (median)	No-VOC	Low-VOC	No Formaldehyde	No Added Toxins or Carcinogens	Renewable Content	Chemicals of Concern
Fiber glass	Johns Manville	Formaldehyde-Free Microlite, ComfortTherm Plastic wrapped	23	Y	Y	Y	33%	30%	5%	x		х	x		
Fiber glass	Johns Manville	Unfaced fiber glass batts and rolls (Canada plant)	27	Y	Y	Y	58%	55%	5%	x		х	x		
Fiber glass	Johns Manville	All fiber glass batts and rolls	23	Y	Y	Y	23%	20%	5%	х		х	х		
Fiber glass	Owens Corning	EcoTouch™ QuietZone® PINK® FIBER GLAS™ Insulation, EcoTouch™			Y	Y	56%	47%	18%	x		x			
Fiber glass	Knauf	Knauf KN series and KB blanket with ECOSE Technology (for use in appliance, industrial, commercial applications)	23			Y	59.0%	59.0%		х		x	Х		
Fiber glass	Knauf	EcoBatt Insulation and Batts, Blankets and Rolls				Y	>50%	>50%		х		х	х		
Fiber glass	Knauf (previously Guardian)	Guardian Fiberglass/ Unfaced Guardian Fiberglass Insulation with ecoGuard Technology				Y				x		x	x		
Mineral Wool	Owens Corning	Thermafiber® SAFB™ FF (Formaldehyde Free)				Y	35%	0%	70%	x		x	x		
Denim/Cotton	Bonded Logic	UltraTouch™ Denim Insulation					80%	80%		х		х	x		
Denim/Cotton	Building Performance Solutions Inc.	Cotton Blanket (Denim Batts) Insulation					85%	85%		x		х	x		

Board														
				Environme	ntal Certificates			Recycled Content			Роли	tants		
Material	Manufacturer	Manufacturer's Product Line		SCS Indoor Advantage Gold	SCS Recycled Content	Greenguard	Total	Post- consumer (median)	Post- industrial (median)		Low-VOC	No Formaldehyde		Chemicals of Concern
Fiber glass	Knauf	Earthwool® Insulation Board				Y	50%			х		х	Х	
Fiber glass	Johns Manville	Insulshield fiberglass board			Y		23%	20%	5%	х		х	х	Formaldeh yde
Mineral board	Thermafiber, Inc.	Rain Barrier (dark fiber) mineral board	41				35%	0%	20%				х	Formaldehyde (traces)
Mineral board	Rorul (Rockwool)	RockBoard 80	9				23%		45%				х	Eormaldeh yde
XPS	Owens Coming	Foamular® 250 Extruded Polystyrene (XPS) Rigid Foam Insulation			Y	Y	10%	0%	20%				х	

Spray (Polyurethan	ie, Soy Polyurethane Foam)														
				Environmental Certificates			Recycled Cont	tent			Pollu	tants		Renewable	Chemicals of
Material	Manufacturer	Manufacturer's Product Line	Pharos	SCS Indoor Advantage	SCS Recycled	Greenguard	Total	Post- consumer (median)	Post-	No-VOC	Low-VOC	No Formaldehyde	No Added Toxins or		Concern
Soy polyurethane spray	Demile c USA	Heatlok Soy foam insulation	15			Y					х	х	х	30%	PBT (flame
foam															retardant)
Polyurethane spray foam	CertainTeed	CertaSpray Closed Cell Foam	14			Y						х			Not fully
															disclosed:

Loose-Fill & Spray	ed (Fiberglass, Cellulose)														
			1	Environmental Certificates Recycled Content Pollutants											
Material	Manufacturer		Pharos	SCS Indoor Advantage Gold	SCS Recycled Content	Greenguard	Total	Post- consumer (median)	Post- industrial (median)	No-VOC	Low-VOC	No Formaldehyde	No Added Toxins or Carcinogens	Renewable Content	Chemicals of Concern
Fiber glass	Owens Corning	ProPink I77 Pink Loosefil Fiberflass Insulation	27		Ŷ	Y	46%	37%	18%	х		х			
Fiberglass	Johns Manville	JM Spider Plus Interlocking Fiber Technology										х			
Fiber glass	Johns Manville	Loose fill fiberglass Insulation, Climate Pro (BIBS option), Attic Protector, CM24, CM26, and many more products	19	Ŷ	Ŷ		28%	25%	5%	x		x			Polypropolene netting
Fiber glass	CertainTeed	Certainteed Optima Fibergalss Blown-in Insulation	18			Y	16%	10%	11%	х		x			Manufacturing toxins (solvents
Cellulose	Western Fibers	Therm-a-Fact Loosefil Cellulose (for attics)	16				85%	85%				x	x		Boric Acid
Cellulose	GreenFiber LLC	Cocoon Loose Fill Low Dust Cellulose Insulation	14		Y		70%	55%	30%			x			Zinc Sulfate and Boric Acid
Cellulose	Advanced Fiber Technology	Advanced Fiber Technology Environmental Choice Cellulose Fill	13				85%				x	x			Zinc Sulfate and Boric Acid
Cellulose	Western Fibers	Therm-a-Fact Craftkote	12				77%								
Fiber glass	Knauf	EcoFill Wx Blowing Insulation				Y	>61.9%	> 61.9%			х	х			Т



Thermoplastic and	Thermoset Membranes (TPO, KEE, EPDM)								
Material	Manufacturer	Product(s)	SRI	Emittance	California Title 24	Coolroof	Energy Star	VOC Content	Heat Welded
KEE	Commercial Innovations	Solar Brite	110	0.81	Y	Y	Y	-	Y
TPO	GAF materials	TPO and EverGuard Extreme	105	0.84 - 0.91	Y	Y	Y	-	N
KEE	Elex	Flex FB Elvaloy (45 Fleece Back)	83 - 109	0.86 - 0.91	Y	Y	Y		Y
KEE	Eberiile	Fibertite Membrane (45-SM)	84 - 110	0.85 - 0.89	Y	N	Y		Y
TPO	Carlisle Syntec Systems	Sure-Weld and Spectro-Weld TPO (White) Reinforced Membrane	86 - 99	0.86 - 0.88	Y	Y	Y		Y
TPO	Firestone	UltraPly TPO (White)	81 - 98	0.83 - 0.85	Y	Y	Y		N
EPDM	Carisle Syntec Systems	EPD M Sure-White	94	0.90	Y	Y	Y	-	N
EPDM	Versico Incorporated	VersiGard White EPDM	94	0.91	Y	Y	Y		N

Modified Bitumen ((SBS)								
Material	Manufacturer	Product(s)	SRI	Emittance	California Title 24	Coolroof	Energy Star	VDC Content	Heat Welded
SBS	Siplast	Paradiene 30 BW and Paradiene 40 BW	90	0.91	Y	Y	N	N	
SBS	Derbigum	DerbiBrite cap sheets	93	0.81	Y	Y	Y	N	
SBS	Gaf Materials	RuberRoid® EnergyCap™ SBS 30 Granule FR	99	0.84	Y	Y	Y	N	
SBS	Certaineed	Fintlastic GMS Coolstar	86	0.90	Y	Y	Y	N	-

Liquid Applied Men	nbranes								
Material	Manufacturer	Product(s)	SRI	Emittance	California Title 24	Coolroof	Energy Star	VOC Content	Heat Welded
PMMA	Siplast	Parapro Roof Membrane Resin (White)	107	0.89	Y	Y	N	LOW	
acrylic elastomer	Karnak Corporation	501 Elasto Brite	109	0.91	Y	Y	Y	LOW	
acrylic elastomer	Roof Guardian Technologies	RG-170 White Elastomeric Finish Coating	109	0.86	Y	Y	Ŷ	LOW (<50 g/L)	
acrylic elastomer	<u>GA</u> F	Topcoat® EnergyCote™ Elastomeric Coating	115 (White only)	0.87 (White only)	Y	Y	Y	LOW	
acrylic elastomer	Henry	HE280DC White Elastomeric Roof Coating	112	0.9	Y	Y	Y	LOW (<25 g/L)	
water-based roof coating	Neptune Coatings Corp.	WetSuit and Reflex Roof Coating System	black	black	N	N	N	NO	
acrylic elastomer	Siplast	PC-227 Elasometric Roof Coating	104	0.88	Y	Y	Ŷ	HIGH	
acrylic elastomer	National Coatings	Acryshield Reflective Roof Coatings (A400, A500, A550, A600)	104 - 108	0.88	Y	Y	Y	LOW	
acrylic elastomer	APOC	232 Insta-Kote™ or 252 Sunwhite Premium Elastomeric Roof Coating	114 - 115	0.89 - 0.95	Y	Y	Y	LOW (<50 g/L)	-
co-polymer elastomeric emulsion	CertainTeed	FlintCoat-W	90	0.91	Y	Y	Y	LOW (47 glL)	-
acrylic elastomer	APOC	258 Re-New It White Elastomeric Rubber Coating	110	0.95	Y	Y	Ŷ	LOW (<50 g/L)	
water-based roof coating	Adec	Re-Ply Coasting System, bright white	85	0.9	Y	Y	Y	HIGH	-

DIVISION 8: DOOR & WINDOWS

Wood I	loors																
					Environmen	ntal Certificates				Recycled Con	ntent		Renewable Mat'ls		Pollutants		
Material	Manufacturer	Core	Manufacturer's Product Line	FSC Certified	FSC % certified	Energy Star	SCS Recycled Content	Green Guard	Composite RC	Post- Consumer	Post- Industrial	RR [Rapidly Renewable] or R [Renewable]	RR Percentage	No- VOC	Low-VOC	No Formaldehyde	Warranty
				Yes, No, N/A, Optional	Percent (%)	Yes, No	Yes, No	Yes, No						Yes,	Yes, No	Yes, No	
Wood Doors	Masonite	Particleboard Core	Authentic Stile & Rail Door w/FSC/UF Free (ASPIRO™ Series)	Y	70%	N	N	N	40%	0%	80%	R		Y		Y	Lifetime (interor application) Exterior not warranted
Wood Doors	Mascnite	Particleboard Core	FlushWood Veneer Door w/ FSC/UF-Free Core	Y	81%	N	Y	N	29%	0%	57%	RR w/ Bamboo Veneer	low	Y		Y	Lifetime (interor application) Exterior
Wood Doors	VT Industries Inc.	Particleboard Core	Flush Wood Veneer Door w/FSC	Y	98%	N	N	Y	N/A	N/A	N/A	R	100%		Y	Y	Life of Installation (interior use)
Wood Doors	Eggers in dustries	Particleboard Core	Flush Door w/ FSC	Y	100%	N	N	N	7%	0%	14%	R		Y		Y	Lifetime (interor application) Exterior not warranted
Wood Doors	VT Industries Inc.	Agrifiber Core	Flush Door	Y	30%	N	N	Y	35%	0%	70%	RR	70%		Y	Y	Life of Installation (interior use)
Wood Doors	ASSA ABLOY Wood Doors	Agrifiber Core	Flush Door	Y	info not available	N	N	Y	35%	0%	70%	RR	70%			Y	Lifetime (interor application) Two Years (exterior use)
Wood Doors	Maiman Fine Architectural Doors (ASSA ABLOY Co.)	Particleboard Core	Thermal Fused Flush Door	Y	info not available	N	Y	Ŷ	50%	20%	60%	R				Y	Life of originical Installation
Wood Doors	Maiman Fine Architectural Doors (ASSA ABLOY Co.)	Particleboard Core	Stile and Rail Door (stained)	Y	info not available	N	Ŷ	Y	35%	0%	70%	R				Y	Lifetime (interor application) Exterior - 1 year
Wood Doors	Graham Wood Doors (ASSA ABLOY Co.)	Particleboard Core	Flush Door	Y		N	N	Y	20%	0%	40%	R				Y	Lifetime (interor application) Two Years (exterior use)
Wood Doors	Eggers Industries	Structural Composite Lumber (SCL)	Flush or Stile and Rail Door	Y	100%	N	N	N	5%	0%	10%	R		Y		Y	Lifetime (interor application) Two Years (exterior use)

Fire L	00 <i>1</i> \$																
					Environmen	tal Certificates				Recycled Cor	itent		Renewable Mat'ls		Pollutants		
				FSC Certified	FSC % certified	Energy Star	SCS Recycled Content		Composite RC	Post- Consumer	Post- Industrial	RR [Rapidly Renewable] or R [Renewable]	RR Percentage	No- VOC	Low-VOC	No Formaldehyde	
Materia	Manufacturer	Core	Manufacturer's Product Line									[renewable]					Warranty
				Yes, No, N/A, Optional	Percent (%)	Yes, No	Yes, No	Yes, No						Yes,	Yes, No	Yes, No	
Fire	Graham Wood Doors (ASSA ABLOY	Mineral Core	Flush Door w/ 45/60/90 min fire	Y		N	N	Y	0%	-		R		Y		Y	Lifetime (interor application)
Retarda	nt <u>Co</u>)		ratings available														Exterior
Wood			-														not warranted
Fire	Eppers Industries	Mineral Core	Stylus (5-ply flush wood door) with 45/90 minute fire	Y		N	N	N	20%	-		R		Y		Y	Life of Original Installation
Retarda	nt		ratings														-
Wood																	

Steel	loors																
					Environmen	ntal Certificates				Recycled Cor	itent		Renewable Mat'ls		Pollutants		
		_		FSC Certified	FSC % certified	Energy Star	SCS Recycled Content	Green Guard	Composite RC	Post- Consumer	Post- Industrial	RR [Rapidly Renewable] or R [Renewable]	RR Percentage	No- VOC	Low-VOC	No Formaldehyde	
Materia	Manufacturer	Core	Manufacturer's Product Line	Yes, No. N/A. Optional	Percent (%)	Yes. No		Yes. No				Inchematica		Yes.	Yes. No	Yes. No	Warranty
					Percent (/a)	105, 110	165, 140	105, 140						105,	165, 140		
Steel	Ceco Doors (ASSA ABLOY Co.)	varies	Trio-E, Stile and Rail Entrance Door, Madera, Medallion,	N/A	-	N	N	Y	59%	54.5%	9%	N/A				N/A	1 year
Doors			Imperial, Legion, Regent, Omega													1 I	1
Steel	Curries Doors (ASSA ABLOY Co.)	varies	Series: 607, 707, 727, 737, 747, 757, 777, 847, 857	N/A		N	N	Y	39%	35.4%	7.4%	N/A			Y	N/A	1 vear
Doors																1	1
Steel	Stiles	varies	Steel Stiffened Core Doors, Composite Core Doors,	N/A	-	N	N	N	27%	23.0%	7.0%	N/A			Y	N/A	3 years
Doors			Temperature Rise Core Doors, Gamma, Lab-Tek, Endura, True Stile and Rail, Clad, Woodgrain Steel doors, Laminate														

DIVISION 8: DOOR & WINDOWS

Aluminum-Clad We	ood Windows														
				Environmental Standar	ds							Recycled	Content		
Manufacturer	Manufacturer's Product Line	Energy Star Northern Climate Compliant	ASHRAE 90.1 2010	SCS Indoor Advantage Gold	SCS Recycled Content	NFRC Label	FSC	SFI			Cumulative RC	Post- Consumer	Post-Industrial	Warranty	Notes
		Yes, No	Yes, No	Yes, No	Yes, No	Yes, No	Yes, No, N/A	Yes, No, N/A or Optional	NFRC Window assembly tested	NFRC U-Factor 24* x 59* Casament					Code requirements for Climate Zone 5A, cold humid (ASHR AE 90.1) or "Northern" climate from Energy
Andersen Windows	200 Series, 400 Series	Y	Y	Y	Y	Y	0*	0'	HP Low-E SmartSun	0.27	2%	0%	4%	20 years on glass 10 years on non-glass	"Over 70% of wood purchased by Andersen is from certified sources such as FSC and SFI. FSC wood can be specified.
Marvin Windows	Double Hung, Casement, Push Out, Picture, Awning, Bow, Bay, Special	Ŷ	Y	N	N	Y	0	0"	1° Tri-pane IG & argon	0.21	8%	2%	12%	10 year (20 year on insulating glass)	Gas contains 20% per-consume recycled content Jor maigr alummu pagines currently uses 15-2%, purchased (pod-consume) scapatoprojek aluminum and 32-5% in-house (per-consume) scapa. Average window composition is 32-6% gass, 32-6% wood and 0.15% aluminum. At species valiable FSD Contentle. V1 aspects except topical hardwoods available SFI centled.
Loewen	Heat-Smart, Heat-Smart X, and various other products	Y	info not available	N	N	Y	0	Y	Triple Sun 240 Dual Low E	0.21		0%	22-29% recycled glass*	20 year insulated glass 20 year wood component on metal clad products	*Applies to Cardinal glass products only
Jeld-Wen Windows & Doors	Custom Wood, W-4500 Wood	Y	Y	N	N	Y	Y	Y	Triple Glazed Argon filled	0.28	5%	0%	10%	20 years	
Pella Corporation	Axiom Casement, Axiom Awning, Double-Hung, Bow & Bay, Slide-By	Y	info not available	N	N	Ŷ	0	0	11/16" SunDefense Dual Low-E IG w/ Argon w/ 3mm glass	0.26	info not availabl	e -	-	20 year non-laminated glass 10 year laminated glass 10 year nonglass components	
Duratherm Window Corporation	Fixed Frame, Store Front, Awning, Out- Swing, In-Swing, TilVTurn, Hopper, Single Hung, Lift/Roll, Window Wall	Y	N	N	N	Y	Ŷ	N	1" IG w/ Argon	0.24		-	-	3 years (extended available on project by project basis)	
Sem co Windows Doors	Variety of product lines & window types	Y	info not available	N	N	Y			3/4" Insul Low-E 366 w/ Argon	0.33			Y	20 years on glass 10 years on non-glass	

Aluminum/Steel															
			1	Environmental Standar	ds						Recycled Cont	lent			
Manufacturer	Manufacturer's Product Line	Energy Star Northern Climate Compliant		SCS Indoor Advantage Gold	SCS Recycled Content	NFRC Label	FSC	SFI			Cumulative RC	Post- Consumer	Post-Industrial	Warranty	Notes
		Yes, No	Yes, No	Yes, No	Yes, No	Yes, No		Yes, No, N/A or Optional	NFRC Window assembly tested	NFRC U-Factor 24" x 59" Casament					Code requirements for Climate Zone 5A, cold humid (ASHRAE 90.1) or "Northern" climate from Energy
Wausau	Projected & Fixed, Casement, Hung & Rolling, Hurricane, Blast, Unitized Curtainwall, Window Wall, Stick Curtainwall	Yes (Fixed can get down to 0.19 U value)	Ŷ	N	N	Y	N/A	N/A	2250i-XLT Casement w/ Triple IG	0.34	-	0%	80% recycled aluminum 10-20% recycled glass	10 year Limited Warranty	Auminum extrusions that contain at least 60% post- industrial recycled content. Glass, steel and hardware components that are composed of high percentages of recycled content.
Crittall Windows	Corporate 2000 range, Berkeley series	Not sure	info not available	N	N	N	N/A	N/A	not tested	not tested	-	100% recycled steel		10 year on frame and finish	Fixed Light Corporate W20 can achieve 0.29 U-Factor, though other operable windows start at 0.35 and above.
Hope's Windows Inc.	Jamestown 175, Landmark 175, University Series, Empire Bronze	Yes (fixed options are available @ 0.29)	info not available	N	N	Y	N/A	N/A	1" IG University Series	0.44 (0.22 center of glass)	-	100% recycled steel		info not available (email out)	
Tubelite	3700 series	Ŷ	Y	N	N	Ŷ	N/A	N/A	1/4" PPG Solarban 60, 0.47" 90% argon filed, 1/4" dear	0.47 to 0.56	-	50% recycled aluminum*	50% recycled aluminum*	info not available	* Special request for higher recycled content of 100% (50% post-consumer 50% pre-consumer) can be provided on individual basis. Center of glass U-factors: 0.20 to 0.48. Overall U-factors: 0.33 to 0.56

Wood Flooring															
			1	Environmental Certificates			Recycled Content		Renew	wable Mat'ls		Pollutan	ls .		
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	Renewable /Renewable /Renewable [R]	Percentage (%)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Wood (reclaimed)	Carlisle Wide Plank Floors	FSC Antique Reclaimed Plank	NA	FSC Certified	nia	100%	100%	0%	R	100%		Y (60 g/L)	Ŷ	Exceeds CARB2 compliance for formaldehyde emissions	
Wood (reclaimed)	Cochran's Lumber & Millw ork Inc.	FSC Recycled: Species: Antique Oak, Horse Country Oak, Antique Chestnut, Tobaccowcod, Antique Heart Pine	NA	FSC Certified	nía	100%	100%	0%	R	100%		NA	NA		
Wood (reclaimed)	Pioneer Millworks	All Products, Engineered & Solid Plank	NA	FSC Certified	Green America	100%	100%	0%	R	100%		Y	Y		Free from infestation
Wood (engineered)	Pioneer Millworks	Reclaimed (Oak, Chestnut, Ash, Elm)	FSC Certified Plywood	FSC Certified	Green America	100%	100%	0%	R	100%		Y	Y		Lifetime Warranty against wear layer delamination
Wood (solid)	Duro Design	White Oak Flooring, Maple Flooring	NA	FSC Certified	n/a	0%	0%	0%	R	100%		Y	Y		25 year structural warranty. 5 year finish warranty.
Wood (solid)	Wheeland Lumber Comp any. Inc.	Oak, Cherry, Ash, Maple, Poplar, Walnut, "Basswood	NA	FSC Certified	SFI, Rainforest Alliance, IWPA (International Wood Products Association)	0%	0%	0%	R	100%			NA		
Wood (engineered)	Carlisle Wide Plank Floors	Engineered Hardwood (Oak, Cherry, Ash, Maple, Hickory, Walnut, Pine)	Plywood	Claim they sustainably harvest wood	nia	0%	0%	0%	R	100%		Y	Y	Exceeds CARB2 compliance for formaldehyde emissions	
Wood (solid)	Mirage Flooring	"Species: Walnut, Cabreuva, Hard Maple, Brazilian Cherry, Red Oak, Sapele Yellow Birch		FSC Certified	CDPH (California Department of Public Health),	0%	0%	0%	R	100%		Y	Y	Compliance with CARB 93120 phase 2	Lifetime structural warranty. 3 year light commerical finish warranty.
Wood (solid)	Bellawood	American Walnut, Ash, Hickory, Maple, Red Qak, White Oak			Green guard Gold (for low chemical emissions)	0%	0%	0%	R	100%			"finish contains formaldehyde		5 year commercial warranty again st defects and finish wear.

Cork															
				Environmental Certificates			Recycled Content			vable Mat'ls		Pollutants	1		
Materia I	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	Renewable [RR] /Renewable [R]	Perc entage (%)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Cork	Expanko Resilient Floorin 9	Heirloom			nía	50%	0%	100	RR	100%	N	Y	Y		15 year warranty against manufacturing effects
Cork / Rubber Blend	Expanko Resilient Floorin 9	XCR4		**SCS Floor Score / Air Quality	nía	6%	0%	11%	RR	70%	N	Y	Y	Cork Rubber blend flooring is more durable than traditional cork flooring.	1 year warranty against defects. 10 year wear
Cork	Expanko Resilient Floorin 9				nía	50%	0%	100%	RR	100%	N	Y	Y		10 year warranty against defects.
Cork	Expanko Resilient Floorin 9	Vallare x		**SCS Floor Score / Air	Green Guard, Green Guard Gold	50%	0%	100%	RR	100%	N	Y	Y		10 year warranty against defects.
Cork	Duro Design	Cork Tile Flooring		FSC Certified	nía	47%	0%	93%	RR	100%	N	Y	Y		25 year structural warranty. 5 year finish warranty.

Enoxy Elegring

Resilient															
				Environmental Certificates			Recycred Content		Renew	vable mat is		Pollutante	5		
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	Rapidly Renewable [RR]	Percentage (%)	No-VOC		No Formaldehyde	Notes	WARRANTY
Resilient	<u>John so nil</u> e	Harmonium xf			Cradle to Cradle Silver, CA Section 01350, Declare, NSF/ANSI 332 Resilient Floor Coverings,U.N. Global Compact	17%	0%	34%	RR	75%		Y (0.10 g/L)	LEED EQ Credit 4 (low- emitting matT)	"USDA BIO BASED PRODUCT CERTIFIED	5 year warranty against defects.
Resilient	Forbo	Marmoleum			Nordic Environmental Label, Environmental Choice Australia, Nature Plus	22%	0%	43%	RR	51%		Ŷ	LEED EQ Credit 4 (low- emitting mat'l)	"USDA BIO BASED PRODUCT CERTIFIED	5 year warranty against defects.
Resilient	Forbo	Marmoleum MCT		SMaRT Certified [4]	Nordic Environmental Label, Umweltzeichen (The Austrian Ecolabel)	22%	0%	43%	RR	51%		Y	LEED EQ Credit 4 (low- emitting mat'l)		5 year warranty against defects.
Resilient	Armstrong	LinoArt Marmorette Sheet		Floor Score Certified	NSF 332 Gold Level Certification	18%	0%	35%	RR	36%		Y	LEED EQ Credit 4 (low- emitting matT)		5 year warranty against defects.

Epoxy Flooring															
				Environmental Certificates			Recycled Content		Renewable Mat'ls	1		Pollutant	\$		
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	Rapidiv Renewable [RR] /Renewable [R]	Perc entage (%)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Ероху	Stonh ard	Stondad GR (High Strength Comercial Flooring)		Floor Score Certified	nía	13%	0%	25%	RR	n/a		Y (33 g/L)	emitting mat'l)	Stonclad GR utilizes 25% recycled glass fillers and a rapidly renewable component to enhance the material	No warranty offered
Ероху	DUR-A-Flex	DUR-A-GARD			nía							Y (10 g/L)			
Ероху	Everlast Epoxy	Everlast® Eco Floor			nía									Product made with vibrant-colored glass chips from recycled glass. However recycled content not	

Vinyl Flooring															
				Environmental Certificates			Recycled Content		Renewable Mat'l	5		Pollutants			
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	Renewable [RR] /Renewable [R]	Percentage (%)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Vinyl	Armstrong	Migrations Bio Based Tile (BBT)	12"x1.2"	Floor Score Certified	NSF 332 Gold Level Certification	20%	0%	40%	RR	2% Bio Based Resin		Ŷ		Recycled limestone makes up 10% of product	5 year warranty against defects
Vinyl	Mannington	BioSpec MD Sheet	6" wide	Floor Score Certified	NSF / ANSI-332 Platinum Level Certification	5%	5%	0%				Y		Anti-Microbial Vinyl Sheet for Healthcare Facilities	10 year limited commercial warranty
Vinyl	Armstrong	Excelon Imperial	12" x 12" x 1/8" or 3/32" Tile	Floor Score Certified	nía	9%	0%	18%				Ŷ			5 year warranty against defects

Rubber Floorin	g													
				Environmental Certificates			Recycled Content			1	Pollutant	\$		
		Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications		Post-consumer (median)	(median)		No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Rubber	Espanko	Reztec	24" x 24" 48" wide x specified length 4.0mm - 9.5 m m thicknesses	"SCS Floor Score	nia	15.75 - 90% depending on color	**4.5 - 90% depending on color	6.3 - 31.5% depending on color						5 Year Warranty. 20 year service life expected. Recycled Tile designed for heavy commercial applications. Highly resistant to moisture.
Rubber	Eco Surfaces	All Products	36" x 36", 18" x 18" (1/4", 1/8"), 48"	SCS Floor Score	redeux reclamation program	22 - 93%	0 - 22.75%	5 - 93%						5 year Warranty
Rubber	Nora	Norapian Unita		Greenguard Indoor Air Quailty, Greenguard Children & Schools	Green Guard Gold, BRE A+ Rating, Umweltzeichen (The Austrian Ecolabel), The Bue Angel, DGNB (German Sustainable Building Council)						Ŷ			5 year Warranty, Other Greenguard Certified products are available however this particular line offers a range of solid colors
Rubber	<u>John sonit</u> e	MicroTone Speckled Rubber Tile	12" x 12" 24" x 24"	Floor Score	Cradle to Cradle Bronze, CA Section 01350, U.N. Global Compact	0%	0%	0%			Ŷ	Ŷ		10 Year Warranty, Rubber Flooring that is designed for use in commercial applications that include food preparation areas.
Rubber	<u>John so nit</u> e	Defant Oil & Grease Resistant Rubber Tile (Raised Round, Hammered, Marbleized Hammered Patterns)	12" x 12" 24" x 24"		CA Section 01350, U.N. Global Compact	0%	0%	0%			Y	Ŷ		10 Year Warranty, Rubber Flooring that is designed for use in commercial applications that include food preparation areas.

Ceramic													
				Environme	ntal Certificates		Recycled Content			Pollu	tants		
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Ceramic	Floor Gres	Florim			EU Ecolabel		0%	**10 - 62%					
Quarry	Metropolitan C eramics	EnviroQuarry			nía	25%	0%	**50%					1 year warranty against defects.
Quarry	Metropolitan Cieramica	Quarry Basics X-Color			SCS Green Squared Certification (Mayflower Red, Auburn, Chestnut Brown)	2.0 - 5.8%	0%	4.0 - 11.6%					1 year warranty against defects.
Ceramic	Datile	Color Wave Tile			nía	22.5%	7.5%	30%	Ŷ				1-year limited warranty against defects
Quarry	Daltile	Quarry Textures			nía	0%	0%	0%	Y				1 year warranty against defects.
Ceramic	Coverings ETC.	Eco-Gres			nia	up to 25%	0%	up tp 50%					No warranties made
Porcelain	Crossville	EcoCycle American a			SCS Green Squared Certification, FloorScore	2.5 - 10%		5 - 20%	Ŷ				1 year warranty against defects.
Quarry	Datile	Quarry Tile			nía	12.4 - 13.2%	0%	24.8 - 26.4%	Ŷ				1 year warranty against defects.
Ceramic	Datile	Keystones			Covering s ETC	0 - 13.45 %	0 - 8.3%	0 - 10.3%			LEED EQ Credit 4 (low- emitting mat1)		1 year warranty against defects.

Terrazzo													
				Environmen	ntal Certificates		Recycled Content			Pollu	tants		
Material	Manufacturer		Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Terrazzo	Coverings ETC.	Eco-Terr Tiles (cement based tile)			nia	50%	10%	80%	Y				No warranties made
Terrazzo	<u>Wausau Til</u> e	Terrazzo Tile Glass Tile (cement based)			nía	50%	33%	33%					Daitile Warranty (1 year against defects)

Slate													
				Environmen	tal Certificates		Recycled Content			Pollut	ants		
Material	Manufacturer		Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Other Environmental Certifications	Cumulative RC	Post-consumer (median)	Post-industrial (median)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
Slate	Vermont Structural Slate	Various States Locally Quarried in Vermont - Color and Tile Size Vary											
Slate	Evergreen Slate Compan y, Inc.	Various States Locally Quarried in Vermont - Color and Tile Size Vary											
Slate	New England Slate Comp any	Various States Locally Quarried in Vermont - Color and Tile Size Vary											
Slate	Vermont Specialty Slate	Various States Locally Quarried in Vermont - Color and Tile Size Vary											
Slate	Camera State Products	Various States Locally Quarried in Vermont - Color and Tile Size Vary											

Carpet																
				Environmental Certificates			1	Recycled Content		Renewable Mat's	3		Polluta	nis		
Material	Manufacturer	Manufacturer's Product Line	Backing System	NSF-140 or SCS Sustainable Choice or SMaRT	Green Label Plus or Floor Score	Cradle-to- Cradle	Cumulative RC	(median)	Post-industrial (median)	/Renewable [R]	Perc entage (%)	No-VOC	Low-VOC	No Formaldehyde	Notes	WARRANTY
								Nylon is recyclable		Nylon is non- renewable						
Carpet	Bentley Mills	High Performance PC (backing system)	Latex Based	NSF Platinum	Y	N		**10%	**30%	N					available with all broad loom products	10 year warranty (surface wear, edge ravel, delamination, tuft bind)
Carpet	Bentley Mills	Select RC Modular Tile	Thermoplastic	NSF Platinum	Y	N		18%	37%	N					available with all tile products	20 year limited warranty (Greenspec)
Carpet		Modular Carpet Tile with GlassBac RE backing	Recycled Vinyl	NSF Platinum	Y	N	Up to 81% (in cluding 35% post-consumer)	35%		N					UL Environment Certified Product	15 year warranty
Carpet	Tandus Centiva	ER3 Modular Tile	100% Recycled	SCS Platinum	Y	N	*45 - 67% (20% post consumer)			N						Lifetime Limited non- prorated warranty
Carpet	Shaw		EcoWorx 100% PVC free thermoplastic	SCS certified for recycled content	Ŷ	Silver		0%	30%	N					** product is designed to be recycled	Limited Lifetime Commercial Wear Warranty.
Carpet	Shaw		EcoWorx 100% PVC free	SCS Platinum	Y	Silver			20%	N					** product is designed to be recycled	Limited Lifetime Commercial Warranty.
Carpet	Mannington Commercial	Modular Tile with Infinity RE backing	Polymer Compound	SCS Platinum	Y	N	**25% (including 10% post consumer)			N					"Manufacturers website states that product is NSF 140 Platinum however there is no record of the product in NSF's database.	 Limited lifetime (delamination, tuft bind, unraveiling, static charge, wear)
Carpet	Lees (Mohawk Company)	Unibond RE Broadloom		NSF Gold	Υ		24% post consumer		24%	Y						Lifetime Warranty
Carpet	Mannington Commercial	UltraBac RE Broadloom	SBR Rubber	NSF/ANSI-140 Platinum	Y	N	10% post consumer	10%		N						Limited lifetime (delamination, tuft bind, unraveiling, static charge, wear)

Acoustical Fiber &	Wood Ceiling Tile											
			Environmental Certificates	Recycled Content			Renewable Mat'ls			Pollutants		
Material	Manufacturer	Manufacturer's Product Line	Various	Cumulative RC	Post- consumer	Post-industrial (median)	Rapidly Renewable [RR] /Renewable [R]	Percentage (%)	No-VOC	Low-VOC	No Formaldehyde	Warranty
Wood Fiber	Armstrong Ceilings NA	Lay-in, Tectum (previously Tonico), Designer, Designer Plus	Declare., GreenSpec	40%	40%	0%	R	43%	Ŷ		info not available	30 year limited
Mineral Fiber	USG Corporation	Frost ClimaPlus, F Fissured, Glacier, Astro ClimaPlus	GreenGuard Gold, USDA Certified Biobased Product	32 - 40%	0 - 2%	63 - 76%	RR	4.5 - 9%	Ŷ		Y	30 year limited
Mineral Fiber	Armstrong Ceilings NA	Ultima HRC & Cirrus HRC	Declare., GreenSpec	48 - 49%	15%	65 - 67%	NA	0%		Y	Y*	30 year limited
Wood	Armstrong Ceilings NA	WoodWorks FSC-certified Cellings	FSC, Green Spec	46%	0%	92%	NA	0%	N/A	N/A	N/A	30 year limited
Mineral Fiber	Certain Teed	Cashmere, Symphony m, Fine Fissured High NRC	GreenCircle	23%	0%	45%	RR	5 - 7%		Y		10 year limited
Mineral Fiber	CertainTeed	Baroque, Fine Fissured, Sand Micro, Vantage 10	GreenCircle	17 - 23%	0%	33 - 45%	RR	7%		Y		1 year limited
Recycled Glass	pinta acoustic	PHONSTOP Ceiling Tile		100%	100%	0%	NA	0%	info not available	info not available	info not available	info not available
Fiberglass	Armstrong Ceilings NA	Optima, Capz, TechZone	Declare., GreenSpec	42%	12%	59%	NA	0%		Y	Y	30 year limited
High Density Fiberglass	CertainTeed	Ecophon Focus Dg, Ds, F	California Specifications Section 0 1350	120%	70%	1	NA	0%		Y		10 year limited
Fiberglass	CertainTeed	Theatre Black F	GreenCircle	33-39%	33-39%	0%	NA	0%		Ŷ		10 year 10- 95 limited
Fiberglass	CertainTeed	Symphony f, Versatone, Open Plan	GreenCircle, California Specifications Section 01350	30-37%	30-37%	0%						10 year 104 95 limited

Gypsum Board													
			Environmental Certific	ates	Recycled Content			Renewable Mat'ls			Pollutants		
Material	Manufacturer	Manufacturer's Product Line	Green Guard (Y/N)	SCS Recycled Content Certified (Y/N)	Cumulative RC	consumer (median)	industrial (median)	Rapidly Renewable [RR] /Renewable [R]	Percentage (%)	No-VOC	Low-VOC	No Formaldehyde	Warranty
Gypsum Board	CertainTeed Gypsum	ProRoc Brand, ProRoc Brand MR Gypsum Board w/ M2Tech	Y	N	58%	16%	83%	NA		Ŷ	N		Limited Warranty
Gypsum Board	CertainTeed Gypsum	ProRoc Moisture and Mold Resistant Gypsum Board w/ M2 Tech	Y	N	0%			N/A		Y			
Gypsum Board	Georgia Padřic Gypsum Board	Dens Armor Plus Abuse-Resistant, Dens Armor Plus High-Performance, Dens Armor Plus Impact Resistant Interior Panel, ToughRock Gypsum Board, ToughRock Fireguard Gypsum Board	Y	N	49%	2%	94%	NA		Y	N		
Gypsum Board	National Gypsum Company	Gold Bond Brand, Gold Bond Brand Fire-Shield, Gold Bond Brand XP Gypsum Board	Y	N	45%	0%	89%	NA		Ŷ	N		
Gypsum Board	USG Corporation	FIBEROCK Brand AR, VHI, VHI Core-Treated, AQUA TOU GH Interior Panel, ClimaTough Exterior Sheathing, Tile Backer Board	N	Y	48%	0%	95%	NA		N/A	N/A		20 Year Limited
Gypsum Board	USG Corporation	SHEETROCK Brand Gypsum Wallboard	Y		52%	5%	94%	NA		N/A	N/A		
Gypsum Board	CertainTeed Gypsum	ProRoc Brand, ProRoc Brand MR Gypsum Board	Y	N	5%	5%	0%	NA		Ŷ	N		

Ceramic Wall T	ïle										
			Environm	ental Certificates	F	Recycled Content		Poll	utants		
Material	Manufacturer		SCS Certified Indoor Advantage Gold	Other	Post- consumer (median)	Post-industrial (median)	No- VOC	Low-VOC	No Toxins or Carcinogens	Notes	WARRANTY
Ceramic	Coverings ETC.	Eco-Gres®				up to 50%					No Warranty (40 Year Lifespan Guarantee)
Ceramic	Crossville		CONTENT	Tile Council of North America (TCNA) Green Squared® Certification, Hydrotect™, FloorScore		5 - 20%					One year commercial warranty
Ceramic	Dattle	Multitude				35.50%	Y				One year limited warrany

Fabric											
			Environm	ental Certificates	Recycled Co	ntent		Poll	utants		
Material	Manufacturer	Manufacturer's Product Line	SCS Certified Indoor Advantage Gold	Other	Post- consumer (median)	Post-industrial (median)	No- VOC	Low-VOC	No Toxins or Carcinogens	Notes	WARRANTY
Wall Covering	<u>Camegie Fabrics</u>	Xorel Fabric and Wall Covering (100% PVC Free)	Ŷ	Crade-to-Crade Silver, Vincotte Level 3/4 (biobased content), USDA Biobased, NSF FACTS Silver Certification				Ŷ		CHPS Certification; LEED EQ Credit 2.2. Low- emitting math; Free Of Chohrine & Plasticizers; Artil Bacteriis; Safely Disposable Free Of Puc, Chohrine, Plasticizers, Heavy Metals; Free Of Topical Finishes, Dioxin; Xorel Meets The Requirements Of Section 01350 Ozone Debit PDC Free	10 year warranty from date of purchase
Wall Covering	Carnegie Fabrics	Biobased Xorel Fabric and Wall Covering (100% PVC Free)	Ŷ	Crade-to-Crade Silver, Vincotte Level 3/4 (biobased content), USDA Biobased, NSF FACTS Gold Certification, Declare™		60 - 85% Biobased Content		Y		Biobased Xorel sourced from rapidly renewable sugarcane plant, instead of fossil fuels; No added finishes; Achieve points in multiple LEED categories – Rapidly Renewable, Indoor Air Quality, Material Transparency and Material Optimization	10 year warranty from date of purchase

Plastic Laminate	& Phenolic Panel										
			Environme	ental Certificates	F	Recycled Content		Poll	utants		
Material	Manufacturer	Manufacturer's Product Line	GREENGUARD (VOC)	Other	Post- consumer (median)	Post-industrial (median)	No- VOC	Low-VOC	Phenol Formaldeh yde (Y/N)	Notes	WARRANTY
Phenolic	Panolam® Surface Systems	ThickLam™ (High Pressure Laminate)	GREEN GAURD Gold (Indoor Air Quality) , GREEN GAURD Gold (Children & Schools) Certified, LEED MR 4, LEED Low Emitting Materials			13 - 17% Post Industrial			"N		1 year warranty against material defects.
Plastic Laminate	<u>Wilson Art</u>		GREEN GAURD (Indoor Air Quality), GREEN GAURD (Children & Schools) Certified	SCS Indoor Advantage Gold,		23%				FSC Material Content Available (needs verification), 10% of material composition comes from Eucalyptus which is a rapidly renewable resource.	1 year warranty against material defects.

DIVISION 9: FINISHES Latex Environmental Certificates Pollutants MPI Green Performance (VOC & Known Carcinogens) No Toxins or Carcinogens SCS Certified Indoor Advantage Gold GreenGuard Green Seal No-VOC Low-VOC Material ufacture Product Line PHAROS LISTED (Y/N) Notes ARRANTY Nstura® Zero-VOC and Zero Emissions Paint, Flat 512, Eggshell 513, Semi- Gloss 514, Aura Waterborne Interior Paint Flat 522, Eggshell 524, Satin 526, Semi-Gloss 528 Latex, Paint Base paint contains zero-VOC. BM Gennex colorant system is also zero- VOC Benjamin Moore Ν 12 ZERO VOC Flat, Pearl, Eggshell, Semi-Gloss Latex, Paint rican Form tina & N N Ν N ufacturing Latex, Primer Inspired Interior Flat, Eggshell, Semi-gloss, Multi-purpose Primer, Chalkboard Y (<3 g/L) N N N N N ime Limited antee provideo Harmony Interior Acrylic Latex Flat, Eggshell, Semi-Gloss; Pro Industrial Zero-VOC Acrylic Gloss, Semi-Gloss Base paint contains zero-VOC. Added colorants may impact VOC content Latex, Paint vin Williams N Y N Υ 12 ""N Latex, Primer Natura® Zero-VOC Prime iamin Moore **N Ν Latex, Paint Olympic Pain Assure™ Interior Paint Flat, Satin, Semi-Gloss Enamel N N **N Base paint contains zero-VOC. Added colorants may impact VOC content atex Paint PG Pittsburgh Paints Pure Performance Base paint contains zero-VOC. Added colorants may impact VOC content Ν Ν N Y 15 ProMar 200 Zero VOC Interior Latex Base paint contains zero-VOC. Added colorants may impact VOC content (Greenspec states up to 2 g/L) atex Paint win Williams Ν Y Y Ν Y Latex Paint PPG Pittsburgh Paints Speedhide Zero VOC Latex, Paint iamin Moore Eco Spec® WB Paint - Primer (372), Flat (373), Eggshel (374), Gloss (376) Ν Y Y 12 ""N Base paint contains low-VOC. BM Gennex colorant system is also zero-VOC Regal Select Interior Paint Flat (547), Matte (548), Eggshell (549), Pearl (550), Semi-Glos (551) Latex Paint Benjamin Moore N N N Y atex, Primer Safarnat Transitional Drima Y (22 g/L) American Form Manufacturing Latex, Primer Walboard Primecoat HPV Y (36 g/L) American Formulating & Manufacturing N atex, Primer Metalcoat Acrylic Primer Y (93 g/L) American Formulating & N Ν N ufacturing ProGreen 200 Low VOC Paint Flat, Low-Sheen, Eggshell, Semi- Gloss, ProGreen 200 Low VOC Paint Primer Latex, Paint **50 g/L Base paint contains low-VOC. Added colorants may impact VOC content Ν Υ 10 "N

			Favironmea	tal Certificates			т	Pollutan	14		1
Material Manufacturer	Product Line	SCS Certified Indoor Advantage Gold	GreenGuard	Green Seal	MPI Green Performance (VOC & Known Carcinogens)	PHAROS LISTED (Y/N)	No-VOC	Low-VOC	No Toxins or Carcinogens	Notes	WARRANT
mponent Water Bona	Bona Traffic	N	Y	N	N			230 g/L			
mponent Water AFM Safeccet	Polyure seal BP	SCS GOLD	N	N	N			283 g/L			
lased Finish Woca.	Diamond Oil	N	N	N	N			6 g/L	Contains Naphtha	available MSDS is European (Denmark)	
mponent Water Bona ed Acrylic Sealer	Bona ClassicSeal	N	Y	N	N			100 g/L		Sealers are used to block tanins from darkening wood flooring. Sealers are applied as a base coat for top coat	
mponent Water Basic Coatings	Street Shoe NXT	N	N	N	N			275 g/L			
			Environmen	tal Certificates				Pollutan	fs		
Material Manufacturer	Product Line	SCS Certified Indoor Advantage Gold	GreenGuard	Green Seal	MPI Green Performance (VOC & Known Carcinogens)	PHAR OS LISTED (Y/N)	No-VOC	Low-VOC	No Toxins or Carcinogens	Notes	WARRANT
er Based Wood AFM Safeccat	DuroStain	SCS GOLD	N	N	N			67 g/L			
er / Soy Based Eco Safety Products d	Timbersoy Wood Stain	N	N	N	N			<10 g/L			
ent Free Oil OSMO ed Wood Stain	Polyx Professional Color Oil	N	N	N	N			<50 g/L			
lased Wood Minwax	Wood Finish 250 VOC Compliant	N	N	N	N			250 g/L			
d ent Free Oil OSMO ed Wood Stain	Polyx Professional Color Oil	N	N	N	N			<50 g/L			

			Environmental Certificates Pollutants									
Material	Manufacturer	Product Line	SCS Certified Indoor Advantage Gold	GreenGuard	Green Seal	MPI Green Performance (VOC & Known Carcinogens)	PHAROS LISTED (Y/N)	No-VOC		No Toxins or Carcinogens	Notes	WARRANTY
Water Based Epoxy	Rustoleum In dustrial	Sierra Performance S40 Water Based Epoxy Floor Coating	N	N	Y	N	12	VOC Free				
	Richard James Specialty Chemicals Corp	200 - Series Epoxy Primer	N	N	N	N			2.35 g/L			
	Richard James Specialty Chemicals Corp	StoneLok E3	N	N	N	N			**97.5 g/L			Warranted to meet manufacturers specs.
	Richard James Specialty Chemicals Corp	StoneLok MLT Plus	N	N	N	N			**100 g/L			

AINT REMOVER									
	FORM	Manufacturer	Product Line	Environmental Certificates			Pollutants		
Material					No-VOC		Sodium Hydroxide, N- MethylPyrrolidone (NMP), Methylene Chloride (also called dichloromethane, or DCM)	Notes	
Water Based (Bio Degradeable) Paint Stripper	Paste, Aerosol	Dumond	Smart Strip ™ Advanced Paint Remover		Y		N	no environmental certificates.	
Water-based (Bio Degradable) Paint Stripper	Liquid or Gel	Eco Safety Products	EcoF ast		Y		N	no hazardous materials present	
Water Based (Bio Degradeable) Paint Stripper	Paste	Dumond	Smart Strip Pro			5% (by weight)	N	no en viro rime ntal certificates.	
Soy Based (Bio Degradeable) Paint Stripper	Gel	Franmar Chemical	Paint & Urethane Stripper (Soy Gel)			49% (578.96 g/L)	NMP		
Soy Based Lead Paint Stripper		Franmar Chemical	Lead Based Paint Stripper (LEAD OUT)			55.7% (513.75 g/L)		no environmental cartificates, however because this product is designed to "solate" heavy metals into a non hazordous state this product should not be compared with other general purpose paint removers. Its VCC content should be viewed as unconsequential as the product products users from lead exposure.	
Soy Based Lead Paint Stripper	Liquid	Eco. Safety Products	Soy It Lead Paint & HD Stripper	EPA DE SIGN FOR THE ENVIRONMENT		<50%		because this product is designed to "axiate" heavy metals into a non hazordous state this product should not be compared with other general purpose paint removers. Its VOC content should be viewed as unconsequential as the product products users from lead exposure.	